

## **Rental – 15,000 Gallon UL-142 Jet-A Storage Tank Specification Datasheet**

- Storage Tank
  - 15,000-gallon aboveground 120” cylindrical double wall UL-142 atmospheric storage tank skid supports (NO Slope), butt welded, bottom ground smooth 18” off center, lifting lugs, and anchor holes in saddle
  - All penetration above the 95% maximum fuel level
  - Internal tank sandblasted SSPC-SP10 with two (2) coats of epoxy lining
  - Exterior tank sandblasted SSPC-SP, one (1) coat primer and two (2) coats polyurethane high gloss finish
  - One (1) 24" manways, two (2) flanged emergency fire vents (primary and interstitial) and atmospheric tank vent with stainless steel riser,
  - Manual gauging hatch with lockable cap and floating suction test port,
  - External rear ladder and optional side mounted ladder with platform to access gauge port and floating suction test cable
  - Approximate weight 25,000 lbs. including equipment and excluding fuel
  - Approximate length 30’
- Overfill Prevention
  - Automatic high-level shut-off system at 95% tank capacity with pre-check
- Floating Suction
  - Aluminum floating suction with stainless steel test cable, check valve and swivel
- Anti-Siphon Protection
  - Anti-siphon prevention and external emergency fire valve
- Gauging
  - Morrison 918 ground level reading tank gauge with high level alarm at 90% tank capacity
  - Manual gauging hatch with lockable cap
- Sump Pump
  - Hand operated tank sump pump with anti-siphon and lockable ball valve
  - Optional fuel sump recovery system
- Other items
  - Kruger interstitial visible leak monitor
  - Backpressure available upon request (Additional Charge)
  - Tank is pressure test, flushed, flowed and shipped under vacuum
  - Tank ships fully decaled and labeled
  - Calibrated gauge stick and strapping\tank chart
  - Grounding lugs
  - Viton butterfly valves



## Pictures of 15,000 Gallon Jet-A Storage Tank



[www.fueltech.com](http://www.fueltech.com)

